Fujitsu recommends Windows® 7.

Data Sheet
Fujitsu LIFEBOOK P702 Notebook

Ultra-Mobile Performance to Go

If you need a versatile and lightweight notebook for your everyday business tasks, the Fujitsu LIFEBOOK P702 should be your first choice. Its small form factor, 30.7 cm (12.1-inch) display and long battery runtime ensure enhanced mobile productivity. The ShockSensor protects your hard disk drive against physical impacts while its robust magnesium lid and various security features guarantee that the notebook is secure both on the move and in the office.

Full performance mobility
Maximum productivity even for the most demanding applications thanks to state-of-the-art technology.
- 3rd generation Intel® Core™i3 or Core™i5 processor with Intel® HM76 chipset

Maximum security
Protect your company data against unauthorized third-party access.
- Advanced Theft Protection (Intel® Anti Theft & Computrace®), integrated SmartCard slot, optional fingerprint sensor, TPM module and OmniPass Security Software

Reliable companion
Secure and effective working even for the most demanding of users in all situations
- Robust and lightweight magnesium lid, ShockSensor, long battery runtime, spill-resistant keyboard
- Optional 0-Watt AC Adapter guarantees that the notebook does not consume electricity when switched off

Ergonomic working
Enhance your user experience with clever ergonomic features.
- ScrollWheel, optional HD webcam, small form factor
- Anytime USB Charge to charge phones/media devices even when the system is turned off

Ultimate connectivity
Stay connected wherever you are; wireless connectivity anytime anywhere, even if there is no hotspot nearby.
- Optional embedded 3G/UMTS or 4G/LTE, WLAN
- Bluetooth® and integrated DisplayPort

Fujitsu recommends Windows® 7.

Components

Processor	Intel® Core™ i5-3210M processor (up to 3.1 GHz 2.5 GHz, 3 MB) *
	Intel® Core™ i5-2450M processor (2.5 GHz, 3 MB) *
	Intel® Core™ i3-2370M processor (2.4 GHz, 3 MB) *
	Intel® Core™ i5-3320M processor (2.6 GHz, 3 MB)
	*Processor only for retail, SMB, education and government
Operating systems	
Operating system	Windows® 7 Professional 64-bit Windows® 7 Home Premium 64-bit Windows® 7 Home Basic (EM) 64-bit
Operating system compatible	Windows® XP 32-bit
Operating system notes	Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via http://support.ts.fujitsu.com
Memory modules	2 GB (1 module(s) 2 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM
	4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM
	8 GB (1 module(s) 8 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM
Base unit memory	LIFEBOOK P702
Supported capacity RAM (min.)	2 GB
Supported capacity RAM (max.)	16 GB
Memory slots total	2
Memory slot type	DIMM (DDR3)
Memory notes	DDR3 - 1600 MHz
Hard disk drives (internal)	SSD SATA III FDE, 128 GB, 2.5-inch
	SSD SATA III, 256 GB, 2.5-inch
	SSD SATA III, 128 GB, 2.5-inch
	SATA, 7200 rpm, 500 GB, 2.5-inch, S.M.A.R.T.
	SATA, 7200 rpm, 320 GB, 2.5-inch, S.M.A.R.T.
	SATA, 5400 rpm, 320 GB, 2.5-inch, S.M.A.R.T.
	FDE, 7200 rpm, 320 GB, 2.5-inch, S.M.A.R.T.
Hard disk notes	ShockSensor for HDD shock protection One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software. Up to 18 GB of HDD space is reserved for system recovery Internal HDD interface: S-ATA III (6GBit/s)
WLAN (optional)	Intel® Centrino® 6205 802.11 a/b/g/n
	Intel® Centrino® Wireless-N2200 b/g/n
Wireless technologies	
Antennas	2 Dual band WLAN antennas, 2 UMTS/LTE antennas optional, 1 Bluetooth antenna optional
WLAN notes	Import and usage according to country-specific regulations.
3G/4G (optional)	Sierra Wireless Gobi 3000 (UMTS downlink speed 14.4 Mbit/s, UMTS uplink speed 5.76 Mbit/s)
	LTE Sierra Wireless MC7710 (UMTS downlink speed up to 100 Mbit/s, UMTS uplink speed up to 50 Mbit/s)
Bluetooth (optional)	Bluetooth 4.0
Display	30.7 cm (12.1-inch), LED backlight, (WXGA), Anti-glare display, magnesium, 1280 x 800 pixel, 300:1, 200 cd/m
Base unit	LIFEBOOK P702

General system information	
Chipset	Intel® HM76
BIOS features	BIOS based on Phoenix SecureCore
Graphics	
TFT resolution (DisplayPort)	up to 2560 x 1600
TFT resolution (VGA)	up to 1920 x 1200
TFT resolution (DVI on Port Replicator)	up to 1920 x 1200
TFT resolution (DisplayPort on Port Replicator)	up to 2560 x 1600
Graphics brand name	Intel® HD Graphics 4000 with 3rd generation Core i processors
Graphics features	3 Display Support
Graphics notes	Shared memory depending on main memory size and operating system
Interfaces	
Memory card slots	1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB)
ExpressCard slots	1 (34 mm supported)
SmartCard slot	1
SIM card slot	1 (usable only with 3G/UMTS, 4G/LTE)
Modem (RJ-11)	
USB 3.0 total	1 (with Anytime USB Charge functionality)
USB 2.0 total	2
VGA	1
DisplayPort	1 (V1.1a)
Ethernet (RJ-45)	1
DC-in	1
Audio: line-in / microphone	1
Audio: line-out / headphone	1
Internal microphones	1 (digital)
Docking connector for Port Replicator	1
Kensington Lock support	1
Wired communication	
LAN	Built-in 10/100/1000 MBit/s Intel® 82579 V
Keyboard and pointing devices	
	Spill-resistant keyboard (new layout)
	Number of keyboard keys: 83, Keyboard pitch: 18 mm, Keyboard stroke: 2.0 mm
	Multi-gesture touchpad with two mouse buttons and ergonomic ScrollWheel Optional: Fingerprint sensor Application buttons
Multimedia	
Audio type	On board
Audio codec	Realtek ALC269
Audio features	Stereo speakers, 1x built-in microphone
Camera	Optional: Built-in HD webcam or Full HD webcam (Microsoft® Lync™) (depending on configuration)
Power supply	
AC Adapter	19 V / 65 W (3.42 A) stick type, 100 V - 240 V (AC Input) , 50 Hz - 60 Hz, Slim and light AC-Adapter
	19 V / 65 W (3.42 A) standard type, 100 V - 240 V (AC Input) , 50 Hz - 60 Hz, Standard Adapter
	19 V / 80 W (4.22 A), 100 V - 240 V (AC Input) , 50 Hz - 60 Hz, Standard Adapter
	19 V / 80 W (4.22 A), 100 V - 240 V (AC Input) , 50 Hz - 60 Hz, 0-Watt AC Adapter technology
Notes	65W AC Adapter for usage with system/ 80W AC Adapter for usage with Port Replicator
1st battery options	Li-Ion battery 6-cell, 6700 mAh, 72 Wh
	Li-Ion battery 6-cell, 5600 or 5800 mAh, 63 Wh
Runtime 1st battery	up to 13 h (tbd)
Battery charging time	~120 min (63Wh) ~ 190 min (72Wh)

Power supply	
Battery notes	Battery runtime information is based on worldwide acknowledged BAPCO Mobile Mark 2007 Benchmark (readers mode e.g. surfing the internet, writing E-mails, viewing documents) which provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity slightly decreases with every charging cycle and over the lifetime.
Power consumption	
Power consumption note	See white paper Energy Consumption
Dimensions / Weight / Environmental	
Dimensions (W x D x H)	283 x 215 x 25 (front) / 32 (rear) mm
Weight	1.48 kg
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	5 - 35°C
Operating relative humidity	20 - 85 %
Additional Software	
Additional software (preinstalled)	Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Power Saving Utility Plugfree Network EasyGuide online user documentation Nero Essentials S (burning software) Norton Internet Security (incl. Firewall) 60 days version Fujitsu Recovery (Hard Disk Based Recovery) Microsoft® Office Starter: reduced-functionality Word and Excel® only, with advertising. No PowerPoint® or Outlook®. Buy Office 2010 to use the full-featured software.
Additional software (optional)	Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS)
Manageability	
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intel® Standard Manageability WoL (Wake on LAN)
Manageability software	DeskView Client DeskView Instant BIOS Management DeskView Integration for Symantec Management Platform
DeskView components	Inventory Management BIOS Management Driver Management Security Management Alarm Management
Supported standards	WMI PXE BootP (made4you)
Manageability link	http://ts.fujitsu.com/solutions/it_infrastructure_solutions/manageability/featurefinder.html
Security	
System protection	Kensington Lock support
Audit proof protection	Advanced Theft Protection (Intel® Anti Theft & Computrace®) Optional: Trusted platform module (TPM 1.2) Norton Internet Security (incl. Firewall) 60 days version

Fujitsu recommends Windows® 7.

Security	
Access protection	Hard disk password Integrated SmartCard slot User and supervisor BIOS password Optional: Integrated fingerprint sensor including Omnipass software

Compliance	
Europe	CE Nordic Swan in progress CB
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) WiFi certified ENERGY STAR® 5.0 EPEAT® Gold (dedicated regions)
China	CCC (depending on configuration)
Compliance notes	Above mentioned compliances are planned but not available at preliminary stage.
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx

Port Replicator interfaces (optional)	
DC-in	1 (supports also 0-Watt AC Adapter)
Power on switch	1
USB 2.0 total	4
DisplayPort	1 (not usable in parallel with DVI)
VGA	1
DVI	1 (not usable in parallel with DisplayPort)
Ethernet (RJ-45)	1
eSATA	1
Notes	Supports 0-Watt AC Adapter technology

Warranty	
Standard Warranty	1 year
Service level	Collect & Return Service / Bring-in Service (depending on country specific requirements)

Maintenance and Support Services - the perfect extension	
Recommended Service	5x9h response time next business day, on-site service
Spare Parts availability	5 years
Service Weblink	http://www.fujitsu.com/fts/services/support

Recommended Accessories

Port Replicator

Flexibility, expandability, desktop replacement, investment protection – to name just a few benefits of Fujitsu docking options. In the office or at home it takes just a second to attach your notebook to the Port Replicator and get connected to your external display, keyboard and mouse, for example. Your workplace is simple and tidy while you are ready to work with your notebook.

Order Code:
S26391-F977-L100

LIFEBOOK bundle (Port rep\AC Adapter\EU-Cable Kit)

The combination of our Port Replicator and AC adapter is the perfect docking solutions for the LIFEBOOK Series and CELSIUS Mobile workstation - our professional notebooks - to simplify your mobile life. In the office or at home it takes just a second to attach your notebook to the Port Replicator and get connected to your peripherals.

Order Code:
S26391-F977-L200

Fujitsu recommends Windows® 7.

More information

Fujitsu platform solutions

In addition to Fujitsu LIFEBOOK P702, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures
With the Fujitsu Dynamic Infrastructures approach,Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructureas-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products
www.fujitsu.com/global/services/computing/

Software
www.fujitsu.com/software/

More information

Learn more about Fujitsu LIFEBOOK P702, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/mobile

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.
Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT.
Please find further information at http://www.fujitsu.com/global/about/environment/

Copyrights

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.
Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

CONTACT
FUJITSU Technology Solutions
Website: www.fujitsu.com/fts
2012-06-03 CE-EN

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.
Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions